



SILENT MINIBAR TECHNOLOGY

*Experience the cool of silence*



[www.ismminibar.com](http://www.ismminibar.com)





ISM Minibar was founded in an area of 7480 square meter in Manisa, 1986. After all the shares were bought by INCI HOLDING in May 2000, ISM Minibar became a part of INCI HOLDING, ([www.inciholding.com](http://www.inciholding.com)) ISM Minibar completed the necessary investments in a very short period by the power of the INCI HOLDING and became one of the top brands in hotel equipment sector.

ISM Minibar is a global company exporting 70% of its products more than 60 countries across 5 continents via its strong network of distributors.

Having been in a leading position in absorption cooling system since its foundation, our company has adopted the main strategic goal of becoming a main producer and supplier both at domestic and abroad markets in the hotel equipment sector.

In line with this goal, as of 2011, our company developed and launched Peltier Seri minibars which have considerably low energy consumption and have 0 dB noise level as absorption type system. We describe Peltier Seri minibars as eco-friendly minibars.

In addition to ISO 9001 Quality and Management Systems certification, ISM MINIBAR became entitled to ISO 14001 Environmental Management System, ISO 45001:2018 Management System Certifications and also has TUV GS, TUV CB, EAC, G-Mark, ROHS, UL and UL NOM product certifications.

ISM Minibar has become a well-known brand in the hotel equipment sector with its fast growing OEM, international and local sales channels, developing R&D projects and efficient after sales services. Minibar has been listed as 'Preferred Supplier' for most of the hotel chains.

We continue to boost our production quality, products, brand popularity and market share in a stable way with an effort to meet the new trends and expand our portfolio.



# PELTIER SERIES



Peltier Technology is based on an effect, which was discovered by the French physicist Peltier in 1834. It occurs when a current is passed through two dissimilar metals or semiconductors that are connected to each other junctions. The current drives a transfer of heat from one junction to the other; one junction cools off while the other heats up; as a result, this effect is used for thermoelectronic cooling.

## PELTIER SERIES STANDARD FEATURES

Led Light	Standard
Automatic Defrost	Standard
Reversible Door	Standard
Curved Door	Standard
Thermostat Control	Electronic
1,5 lt Bottle Holder Shelf	Standard (for 401,521,601) Transparent / White Plastic

## COLOR RANGE



Black



White



Grey (Metallic)



Sliding hinge for built in use



Transparent shelves



Intelligent LED Light



Special designed evaporator



1,5 LT Bottle holder (40 LT/52 LT/60LT)



Reversible door



Lock (Optional)



## SM 40 DM

Gross Volume	44
Net Volume	41
External Dimensions (HxWxD/mm)	417 x 549 x 483
Packed Dimensions (HxWxD/mm)	465 x 590 x 515
Compartment Type	Kiler / Cellar
Cooling System	Thermoelectric
Energy Consumption (kWh/Year)	120
Energy Efficiency Index (EEI)	97
Climate Class	N (16C°-32C°)
Storage Temperature	8 - 14 °C
Gross Weight	16,50 kg
Net Weight	15,20 kg
Power	60 W
Voltage / Frequency	100-240 V / 50-60 Hz.
*Container Loading Capacity 20'/40'/40'HC"	144 - 304 - 304



## SM 271 TH - SM 271 THG



	SM 271 TH	SM 271 THG
Gross Volume	24	28
Net Volume	23	27
External Dimensions (HxWxD/mm)	512 x 384 x 397	
Packed Dimensions (HxWxD/mm)	559 x 432 x 464	
Compartment Type	Kiler / Cellar	
Cooling System	Thermoelectric	
Energy Consumption (kWh/Year)	92	175
Energy Efficiency Index (EEI)	118	223
Climate Class	N (16°C-32°C)	
Storage Temperature	8 - 14 °C	
Gross Weight	10,75 kg	13,25 kg
Net Weight	9,45 kg	11,95 kg
Power	60 W	
Voltage / Frequency	100-240 V / 50-60 Hz.	
*Container Loading Capacity 20'/40'/40'HC"	260 - 520 - 520	

## SM 301 TH - SM 301 THG

	SM 301 TH	SM 301 THG
Gross Volume	30	35
Net Volume	28	31
External Dimensions (HxWxD/mm)	512 x 419 x 397	
Packed Dimensions (HxWxD/mm)	559 x 442 x 464	
Compartment Type	Kiler / Cellar	
Cooling System	Thermoelectric	
Energy Consumption (kWh/Year)	92	191
Energy Efficiency Index (EEI)	117	242
Climate Class	N (16°C-32°C)	
Storage Temperature	8 - 14 °C	
Gross Weight	11,50 kg	14,00 kg
Net Weight	10,20 kg	12,70 kg
Power	60 W	
Voltage / Frequency	100-240 V / 50-60 Hz.	
*Container Loading Capacity 20'/40'/40'HC"	260 - 520 - 520	



## SM 401 TH - SM 401 THG



	SM 401 TH	SM 401 THG
Gross Volume	38	44
Net Volume	33	40
External Dimensions (HxWxD/mm)	566 x 441 x 432	
Packed Dimensions (HxWxD/mm)	614 x 464 x 494	
Compartment Type	Kiler / Cellar	
Cooling System	Thermoelectric	
Energy Consumption (kWh/Year)	97	295
Energy Efficiency Index (EEI)	123	371
Climate Class	N (16°C-32°C)	
Storage Temperature	8 - 14 °C	
Gross Weight	12,85 kg	15,85 kg
Net Weight	11,55 kg	14,55 kg
Power	60 W	
Voltage / Frequency	100-240 V / 50-60 Hz.	
*Container Loading Capacity 20'/40'/40'HC"	165 - 360 - 480	

# PELTIER SERIES



## SM 521-TH

Gross Volume	43
Net Volume	38
External Dimensions (HxWxD/mm)	610 x 441 x 432
Packed Dimensions (HxWxD/mm)	659 x 464 x 494
Compartment Type	Kiler / Cellar
Cooling System	Thermoelectric
Energy Consumption (kWh/Year)	109
Energy Efficiency Index (EEI)	137
Climate Class	N (16°C-32°C)
Storage Temperature	8 - 14 °C
Gross Weight	13,75 kg
Net Weight	12,45 kg
Power	60 W
Voltage / Frequency	100-240 V / 50-60 Hz.
"Container Loading Capacity 20'/40'/40'HC"	165 - 360 - 450

## SM 601-TH

Gross Volume	54
Net Volume	48
External Dimensions (HxWxD/mm)	566 x 477 x 497
Packed Dimensions (HxWxD/mm)	623 x 499 x 554
Compartment Type	Kiler / Cellar
Cooling System	Thermoelectric
Energy Consumption (kWh/Year)	192
Energy Efficiency Index (EEI)	210
Climate Class	N (16°C-32°C)
Storage Temperature	8 - 14 °C
Gross Weight	14,85 kg
Net Weight	13,55 kg
Power	60 W
Voltage / Frequency	100-240 V / 50-60 Hz.
"Container Loading Capacity 20'/40'/40'HC"	132 - 276 - 368



# PLATINUM SERIES

## COLOR RANGE



Black



White



Grey (Metallic)



Sliding hinge for built in use



Transparent shelves



Intelligent LED Light



1,5 LT Bottle holder (40 LT/52 LT/60LT)



Reversible door



Lock (Optional)

## STANDARD FEATURES

	SM 301	SM 401
Led Light	Standard	Standard
Automatic Defrost	Standard	Standard
Reversible Door	Standard	Standard
Curved Door	Standard	Standard
Thermostat Control	Electronic	Electronic
1,5 Lt Bottle Holder	N/A	Yes
Shelf	Blue Transparent	Blue Transparent

### SM 301

Gross Volume	30
Net Volume	26
External Dimensions (HxWxD/mm)	512 x 419 x 423
Packed Dimensions (HxWxD/mm)	559 x 442 x 464
Compartment Type	Kiler / Cellar
Cooling System	Absorption
Energy Consumption (kWh/Year)	256
Energy Efficiency Index (EEI)	102,6
Climate Class	N (16C°-32C°)
Storage Temperature	8 - 14 °C
Gross Weight	13,00 kg
Net Weight	11,70 kg
Power	60 W
Voltage / Frequency	110 V or 230 V / 50-60 Hz.
*Container Loading Capacity	20'/40'/40'HC"
	260 - 520 - 520



### SM 401

Gross Volume	38
Net Volume	33
External Dimensions (HxWxD/mm)	566 x 441 x 457
Packed Dimensions (HxWxD/mm)	614 x 464 x 494
Compartment Type	Kiler / Cellar
Cooling System	Absorption
Energy Consumption (kWh/Year)	263
Energy Efficiency Index (EEI)	105,1
Climate Class	N (16C°-32C°)
Storage Temperature	8 - 14 °C
Gross Weight	14,20 kg
Net Weight	12,90 kg
Power	60 W
Voltage / Frequency	110 V or 230 V / 50-60 Hz.
*Container Loading Capacity	20'/40'/40'HC"
	165 - 360 - 480



# UNIQUE SERIES

## STANDARD FEATURES

Led Light  
Automatic Defrost  
Reversible Door  
Curved Door  
Thermostat Control  
1,5 lt Bottle Holder  
Shelf

Standard  
Standard  
Standard  
Standard  
Electronic  
N/A  
Transparent

## OPTIONAL FEATURES

Energy Supply (110V/60Hz - 12/230V - 12/110V - 24/230V)  
Lock  
Wheels  
Glass door / Chromium door  
Inox  
Sliding hinge for free standing models  
Free standing  
Built in

## SM 307

## COLOR RANGE



Black



White



Grey (Metallic)

Gross Volume	33
Net Volume	28
External Dimensions (HxWxD/mm)	511 x 441 x 457
Packed Dimensions (HxWxD/mm)	559 x 464 x 494
Compartment Type	Kiler / Cellar
Cooling System	Absorption
Energy Consumption (kWh/Year)	247
Climate Class	N (16°C-32°C)
Storage Temperature	8 - 14 °C
Gross Weight	14,80 kg
Net Weight	13,5 kg
Power	60 W
Voltage / Frequency	110 V or 230 V / 50-60 Hz.
"Container Loading Capacity 20°/40°/40°HC"	165 - 360 - 480



# UNIQUE SERIES



1,5 LT Bottle holder  
(40 LT/52 LT/60LT)



Sliding hinge for  
built in use



Intelligent LED Light



Lock (Optional)



Reversible door



Transparent shelves

## SM 407

Gross Volume	37
Net Volume	33
External Dimensions (HxWxD/mm)	566 x 441 x 457
Packed Dimensions (HxWxD/mm)	614 x 464 x 494
Compartment Type	Kiler / Cellar
Cooling System	Absorption
Energy Consumption (kWh/Year)	274
Climate Class	N (16C°-32C°)
Storage Temperature	8 - 14 °C
Gross Weight	15,30 kg
Net Weight	14,00 kg
Power	60 W
Voltage / Frequency	230 V / 50 - 60 Hz.
*Container Loading Capacity 20°/40°/40°HC"	165 - 360 - 480



# ECO SERIES



## COLOR RANGE



Black



White



Grey (Metallic)



Lock (Optional)



Intelligent LED Light



Sliding hinge for built in use

## STANDARD FEATURES

Led Light	N/A
Automatic Defrost	Optional
Reversible Door	Standard
Curved Door	Standard
Thermostat Control	Mechanic
1,5 lt Bottle Holder	Standard
Shelf	White Plastic

## SM 27 ECO

Gross Volume	24
Net Volume	21
External Dimensions (HxWxD/mm)	512 x 390 x 423
Packed Dimensions (HxWxD/mm)	559 x 432 x 464
Compartment Type	Killer / Cellar
Cooling System	Absorption
Energy Consumption (kWh/Year)	226
Energy Efficiency Index (EEI)	290
Climate Class	N (16C°-32C°)
Storage Temperature	2 - 14 °C
Gross Weight	11,45 kg
Net Weight	10,15 kg
Power	60 W
Voltage / Frequency	110 V or 230 V / 50-60 Hz.
"Container Loading Capacity 20°/40°/40°HC"	260 - 520 - 520



## STANDARD FEATURES

Led Light	N/A
Automatic Defrost	Optional
Reversible Door	Standard
Curved Door	Standard
Thermostat Control	Mechanic
1,5 lt Bottle Holder	N/A
Shelf	White Plastic



## SM 30 ECO

Gross Volume	30
Net Volume	26
External Dimensions (HxWxD/mm)	512 x 419 x 423
Packed Dimensions (HxWxD/mm)	559 x 442 x 464
Compartment Type	Kiler / Cellar
Cooling System	Absorption
Energy Consumption (kWh/Year)	226
Energy Efficiency Index (EEI)	288
Climate Class	N (16C°-32C°)
Storage Temperature	2 - 14 °C
Gross Weight	11,80 kg
Net Weight	10,50 kg
Power	60 W
Voltage / Frequency	110 or 230 V / 50-60 Hz.
*Container Loading Capacity 20'/40'/40"HC"	260 - 520 - 520

## STANDARD FEATURES

Led Light	N/A
Automatic Defrost	Optional
Reversible Door	Standard
Curved Door	Standard
Thermostat Control	Mechanic
1,5 lt Bottle Holder	Yes
Shelf	White Plastic



## SM 40 ECO

Gross Volume	38
Net Volume	33
External Dimensions (HxWxD/mm)	566 x 441 x 457
Packed Dimensions (HxWxD/mm)	614 x 464 x 494
Compartment Type	Kiler / Cellar
Cooling System	Absorption
Energy Consumption (kWh/Year)	230
Energy Efficiency Index (EEI)	291
Climate Class	N (16C°-32C°)
Storage Temperature	2 - 14 °C
Gross Weight	13,30 kg
Net Weight	12,00 kg
Power	60 W
Voltage / Frequency	110 or 230 V / 50-60 Hz.
*Container Loading Capacity 20'/40'/40"HC"	165 - 360 - 480

# HAIR DRYERS



## HD H 23

- Two Colour Option: Black / White
- 1200W Power
- 2 Level Speed Adjustment
- 2 Level Heat Adjustment
- Easy Wall Mounting
- Fixation Screws and Secrew Anchors
- 87 m<sup>3</sup>/h Air Flow
- 685 gr Product Weight
- 1 Year Warranty



## HD H 24

- Elegant Design with Chorme Plated Parts
- 1600W Power /Black
- 2 Level Speed Adjustment
- 3 Level Heat Adjustment
- Easy Wall Mounting
- Air Collector
- Fixation Screws and Secrew Anchors
- 87 m<sup>3</sup>/h Air Flow
- 1.188 gr Product Weight (With Shaver Socket)
- 1 Year Warranty



## HD H 24S

- Elegant Design with Chorme Plated Parts
- 1600W Power /White
- 2 Level Speed Adjustment
- 3 Level Heat Adjustment
- Easy Wall Mounting
- Air Collector
- Fixation Screws and Secrew Anchors
- 87 m<sup>3</sup>/h Air Flow
- 1.188 gr Product Weight (With Shaver Socket)
- 1 Year Warranty

# SAFE BOX



## ISM T2-2C

Color: Ivory / Black  
External Dimensions (HxWxD) 220x400x420 mm  
Motorized Lock  
6 Digit Display  
4-6 Digit Password Identification  
6 Digit Master Code  
(To be able to open the safe in emergency situations)  
Manual Master Key  
Password Masking/De-masking Option  
(While autolock when entered 4 wrong passwords)  
100 Last Transaction Memory  
Battery status display (weak,full)  
Assembly to behind or bottom  
Carpet Floor  
4 Batteries  
Corrosion-resistant powder coating





EAC

CE



**ISM MAKİNE ELEKTRİK SANAYİ VE TİCARET A.Ş.**

Anafartalar Cad. No:1 Organize Sanayi Bölgesi 45030 Manisa, TÜRKİYE

Tel : +90. 236 233 42 33 E-Mail : sales@ismas.com.tr

**in** ismminibar



ism-minibar



ism\_minibar